

TECHNICAL SPECIFICATIONS OF DSLR CAMERA (BODY WITH LENS AND ACCESSORIES)

Image Sensor Type	APS-C CMOS sensor
Image Sensor Size	Approx. 22.3 x 14.8 mm
Effective Pixels	Approx. 32.5 megapixels
Image Type	JPEG, RAW (14-bit Canon original), RAW+JPEG & C-RAW +JPEG simultaneous recording possible
Pixels Recorded	Still Images RAW/C-RAW/Large: Approx. 32.3 megapixels (6960 x 4640) Medium: Approx. 15.4 megapixels (4800 x 3200) Small 1: Approx. 8.1 megapixels (3472 x 2320) Small 2: Approx. 3.8 megapixels (2400 x 1600)
	Movies 4K/4K (3840 x 2160) Timelapse: 29.97p/25p Full HD (1920 x 1080): 119.88p/100p/59.94p/50p/29.97p/25p Full HD (1920 x 1080) Timelapse: 29.97p/25p HD (1280 x 720): 59.94p/50p HDR movies (1920 x 1080): 29.97p/25p
LCD Monitor Type	3.0", (3:2), vari-angle, TFT color, liquid-crystal touch screen monitor with approx. 1.04 million dots
Viewfinder Shooting	AF Points 45 (Cross-type AF point: Max 45 points) Focusing Brightness Range EV -3 to 18 (with the center AF point supporting f/2.8, One-Shot AF, at room temperature, ISO 100) Focus Operation One-Shot AF, AI Servo AF, AI Focus AF, Manual Focusing (MF) Shutter Speed 1/8000 sec. to 30 sec., bulb, X-sync at 1/250 sec. Continuous Shooting Speed Max. approx. 10 shots/sec Exposure Compensation ± 5 stops in 1/3- or 1/2-stop increments
Live View Shooting	Focus Method Dual Pixel CMOS AF AF Method Face+Tracking (Eye Detection AF selectable), Spot AF, 1-point AF, Zone AF Focusing Brightness Range EV-5 to 18 (f/1.2, centre AF point, one-shot AF, at room temperature, ISO 100) Available AF Positions Max. up to 5,481 (When selected with the multi-controllers) Shutter Speed 1/16000 sec. to 30 sec. (1/16000 – 1/10000 sec. for electronic shutter), bulb, X-sync at 1/250 sec. Continuous Shooting speed Max. approx. 11 shots/sec (AF Fixed), 7 shots/sec (AF Tracking) Exposure Compensation ± 3 stops in 1/3- or 1/2-stop increments
Metering Mode (Viewfinder Shooting)	216-zone TTL full-aperture metering with an approx. 220,000-pixel RGB+IR metering sensor
ISO Speed (Recommended Exposure Index)	Basic zone: ISO set automatically P, Tv, Av, M, B: ISO Auto, ISO 100 - ISO 25600 set manually (1/3-

	or 1-stop increments and ISO expansion to H (equivalent to ISO 512000)) Movie recording: ISO Auto, ISO 100 - ISO 12800 set manually (1/3- or 1-stop increments and ISO expansion to H (equivalent to ISO 25600)) HDR movies: ISO set automatically
Built-in Flash	Retractable manual pop-up flash, guide no: approx. 12 (ISO 100, meters)
Other Features	Wi-Fi, Bluetooth Low Energy Technology
Dimensions (CIPA Compliant) (W X H X D)	140.7 x 104.8 x 76.8mm
Weight (CIPA Compliant)	Approx. 701g (including battery pack and card)
Accessories	Battery (lithium-ion), charger, 64GB Extreme Pro 220mb/s card With 18-135 IS USM Lens
Warranty	Three (3) Year on parts and services

Prepared by


ROBERTO M. TIONGCO
 Budget Officer


RYAN T. ARENAS
 Computer Operator II